



## Overload relay, 0.6-1A, 1N/O+1N/C

**Part no.** ZB32-1  
**Catalog No.** 278446  
**Eaton Catalog No.** XTOB001CC1  
**EL-Nummer** 0004131841  
**(Norway)**



Powering Business Worldwide™

## Delivery program

Product range	Overload relay ZB up to 150 A		
Product range	Accessories		
Accessories	Overload relays		
Frame size	ZB32		
Phase-failure sensitivity	IEC/EN 60947, VDE 0660 Part 102		
Description	Test/off button Reset pushbutton manual/auto Trip-free release		
Mounting type	Direct mounting		
	I <sub>r</sub>	A	0.6 - 1
Contact sequence			
<b>Auxiliary contacts</b>			
N/O = Normally open	1 N/O		
N/C = Normally closed	1 N/C		
For use with	DILM17, DILM25, DILM32, DILM38, DILMF8, DILMF11, DILMF14, DILMF17, DILMF25, DILMF32, DIULM17, DIULM25, DIULM32, SDAINLM30, SDAINLM45, SDAINLM55		
<b>Short-circuit protection</b>			
Type "1" coordination	gG/gL	A	25
Type "2" coordination	gG/gL	A	4

## Notes

Overload release: tripping class 10 A

short-circuit protective device: Observe the maximum permissible fuse of the contactor with direct device mounting.



Suitable for protection of Ex e-motors.



II(2)G [Ex d] [Ex e] [Ex px], II(2)D [Ex p] [Ex t]

**Notes**

Fitted directly to the contactor

1 Contactor  
2 Bases**Separate mounting****Technical data****General**

Standards	IEC/EN 60947, VDE 0660, UL, CSA		
Climatic proofing	Damp heat, constant, to IEC 60068-2-78 Damp heat, cyclic, to IEC 60068-2-30		
Ambient temperature	Operating range to IEC/EN 60947 PTB: -5 °C - +55 °C		
Open	°C	-25 - +55	
Enclosed	°C	-25 - 40	
Temperature compensation	Continuous		
Weight	kg	0.142	
Mechanical shock resistance	g	10 Sinusoidal Shock duration 10 ms	
Degree of Protection	IP20		
Protection against direct contact when actuated from front (EN 50274)	Finger and back-of-hand proof		

**Main conducting paths**

Rated impulse withstand voltage	U <sub>imp</sub>	V AC	6000
Oversupply category/pollution degree			III/3
Rated insulation voltage	U <sub>i</sub>	V	690
Rated operational voltage	U <sub>e</sub>	V AC	690
Safe isolation to EN 61140			
Between auxiliary contacts and main contacts		V AC	440
Between main circuits		V AC	440
Temperatur compensation residual error > 40 °C			≤ 0.25 %/K
Current heat loss (3 conductors)			
Lower value of the setting range		W	2.5
Maximum setting		W	6.9
Terminal capacities		mm <sup>2</sup>	
Solid		mm <sup>2</sup>	1 x (1 - 6) 2 x (1 - 6)
Flexible with ferrule		mm <sup>2</sup>	1 x (1 - 4) 2 x (1 - 4)
Solid or stranded		AWG	18 - 8
Terminal screw			M4
Tightening torque		Nm	1.8
Stripping length		mm	10
Tools			

Pozidriv screwdriver	Size	2
Standard screwdriver	mm	1 x 6
<b>Auxiliary and control circuits</b>		
Rated impulse withstand voltage	$U_{imp}$	V 4000
Overtoltage category/pollution degree		III/3
Terminal capacities		mm <sup>2</sup>
Solid		mm <sup>2</sup> 1 x (0.75 - 4) 2 x (0.75 - 4)
Flexible with ferrule		mm <sup>2</sup> 1 x (0.75 - 2.5) 2 x (0.75 - 2.5)
Solid or stranded		AWG 2 x (18 - 14)
Terminal screw		M3.5
Tightening torque		Nm 1.2
Stripping length		mm 8
Tools		
Pozidriv screwdriver		Size 2
Standard screwdriver		mm 1 x 6
Rated insulation voltage	$U_i$	V AC 500
Rated operational voltage	$U_e$	V AC 500
Safe isolation to EN 61140		
between the auxiliary contacts		V AC 240
Conventional thermal current	$I_{th}$	A 6
Rated operational current	$I_e$	A
AC-15		
Make contact		
120 V	$I_e$	A 1.5
220 V 230 V 240 V	$I_e$	A 1.5
380 V 400 V 415 V	$I_e$	A 0.5
500 V	$I_e$	A 0.5
Break contact		
120 V	$I_e$	A 1.5
220 V 230 V 240 V	$I_e$	A 1.5
380 V 400 V 415 V	$I_e$	A 0.9
500 V	$I_e$	A 0.8
DC L/R $\leq$ 15 ms		
		Switch-on and switch-off conditions based on DC-13, time constant as specified.
24 V	$I_e$	A 0.9
60 V	$I_e$	A 0.75
110 V	$I_e$	A 0.4
220 V	$I_e$	A 0.2
Short-circuit rating without welding		
max. fuse		A gG/gL 6

## Notes

**Notes** Ambient air temperature: Operating range to IEC/EN 60947, PTB: -5°C to +55°C  
Main circuits terminal capacity solid and flexible conductors with ferrules: When using 2 conductors use equal cross-sections.

## Rating data for approved types

Auxiliary contacts			
Pilot Duty			
AC operated			B300 at opposite polarity B600 at same polarity
DC operated			R300
Short Circuit Current Rating		SCCR	
600 V High Fault			
SCCR (fuse)		kA	100
max. Fuse		A	1 Class J/CC

## Design verification as per IEC/EN 61439

Technical data for design verification			
Rated operational current for specified heat dissipation	I <sub>n</sub>	A	1
Heat dissipation per pole, current-dependent	P <sub>vid</sub>	W	2.3
Equipment heat dissipation, current-dependent	P <sub>vid</sub>	W	6.9
Static heat dissipation, non-current-dependent	P <sub>vs</sub>	W	0
Heat dissipation capacity	P <sub>diss</sub>	W	0
Operating ambient temperature min.		°C	-25
Operating ambient temperature max.		°C	55
IEC/EN 61439 design verification			
10.2 Strength of materials and parts			
10.2.2 Corrosion resistance			Meets the product standard's requirements.
10.2.3.1 Verification of thermal stability of enclosures			Meets the product standard's requirements.
10.2.3.2 Verification of resistance of insulating materials to normal heat			Meets the product standard's requirements.
10.2.3.3 Verification of resistance of insulating materials to abnormal heat and fire due to internal electric effects			Meets the product standard's requirements.
10.2.4 Resistance to ultra-violet (UV) radiation			Meets the product standard's requirements.
10.2.5 Lifting			Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 Mechanical impact			Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 Inscriptions			Meets the product standard's requirements.
10.3 Degree of protection of ASSEMBLIES			Does not apply, since the entire switchgear needs to be evaluated.
10.4 Clearances and creepage distances			Meets the product standard's requirements.
10.5 Protection against electric shock			Does not apply, since the entire switchgear needs to be evaluated.
10.6 Incorporation of switching devices and components			Does not apply, since the entire switchgear needs to be evaluated.
10.7 Internal electrical circuits and connections			Is the panel builder's responsibility.
10.8 Connections for external conductors			Is the panel builder's responsibility.
10.9 Insulation properties			
10.9.2 Power-frequency electric strength			Is the panel builder's responsibility.
10.9.3 Impulse withstand voltage			Is the panel builder's responsibility.
10.9.4 Testing of enclosures made of insulating material			Is the panel builder's responsibility.
10.10 Temperature rise			The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 Short-circuit rating			Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 Electromagnetic compatibility			Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 Mechanical function			The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

## Technical data ETIM 7.0


Low-voltage industrial components (EG000017) / Thermal overload relay (EC000106)		
Electric engineering, automation, process control engineering / Low-voltage switch technology / Overload protection device / Thermal overload relay (ecl@ss10.0.1-27-37-15-01 [AKF075014])		
Adjustable current range	A	0.6 - 1
Max. rated operation voltage U <sub>e</sub>	V	690
Mounting method		Direct attachment
Type of electrical connection of main circuit		Screw connection
Number of auxiliary contacts as normally closed contact		1
Number of auxiliary contacts as normally open contact		1
Number of auxiliary contacts as change-over contact		0
Release class		CLASS 10
Reset function input		No
Reset function automatic		Yes
Reset function push-button		Yes

## Approvals

Product Standards		IEC/EN 60947-4-1; UL 60947-4-1; CSA - C22.2 No. 60947-4-1-14; CE marking
UL File No.		E29184

UL Category Control No.	NKCR
CSA File No.	12528
CSA Class No.	3211-03
North America Certification	UL listed, CSA certified
Specially designed for North America	No
Suitable for	Branch circuits
Max. Voltage Rating	600 V AC
Degree of Protection	IEC: IP20, UL/CSA Type: -

## Characteristics




These tripping characteristics are mean values of the spreads at 20 °C ambient air temperature in a cold state.

Tripping time depends on response current.


When the devices are at operational temperature the tripping time of the overload relay falls to approx. 25 % of the read off value.

- 1: Minimum level, 3-phase
- 2: Maximum level, 3-phase
- 3: Minimum marker, 2-phase
- 4: Highest marker, 2-phase


## Dimensions



① OFF  
 ② Reset/ON



With base ZB32-XEZ



ZB32... + DILM

## Additional product information (links)

**IL03407015Z (AWA2300-2114) Overload relay**

[ftp://ftp.moeller.net/DOCUMENTATION/AWA\\_INSTRUCTIONS/IL03407015Z2018\\_04.pdf](ftp://ftp.moeller.net/DOCUMENTATION/AWA_INSTRUCTIONS/IL03407015Z2018_04.pdf)

**IL03407195Z Sealable shroud**

**IL03407195Z Sealable shroud**

[ftp://ftp.moeller.net/DOCUMENTATION/AWA\\_INSTRUCTIONS/IL03407195Z2018\\_06.pdf](ftp://ftp.moeller.net/DOCUMENTATION/AWA_INSTRUCTIONS/IL03407195Z2018_06.pdf)

**MN03407004Z (AWB2300-1527D/GB) ZB12/XTOB...BC1 and ZB32/XTOB...CC1 overload relays, overload monitoring of Ex e motors**

**MN03407004Z (AWB2300-1527D/GB) ZB12/XTOB...BC1 and ZB32/XTOB...CC1 overload relays, overload monitoring of Ex e motors - Deutsch / English**

[ftp://ftp.moeller.net/DOCUMENTATION/AWB\\_MANUALS/MN03407004Z\\_DE\\_EN.pdf](ftp://ftp.moeller.net/DOCUMENTATION/AWB_MANUALS/MN03407004Z_DE_EN.pdf)