

**MNX PC 150/35 LT**



Sample photo

**Order symbol:** PC 150/35 LT  
**Product nbr:** 6012913  
**Description:** Enclosure, PC  
**Remarks:** Smoked transparent cover

**EAN:** 6418074022370  
**EI. number:**  
 Finland: 3420451  
 Electric No. Denmark: 8212022425  
 Electric No. Italy: 7352070  
 Electric No. Sweden: 2535639

Including: Base with TPE gasket, screws for mounting plate/DIN-rail and cover with polyamide cover screws.

Dimensions:	Length	Width	Height	Accessories:
mm:	180	130	35	MIN 10 DIN-15 Mounting rail
inch:	7.1	5.1	1.4	MIN 15 DIN-15 Mounting rail

Materials:		
<b>Material:</b>	Polycarbonate	MIV 10 DIN-35 Mounting rail
<b>Base colour:</b>	RAL 7035 -light grey	MIV 15 DIN-35 Mounting rail
<b>Cover screws material:</b>	Polyamide	FP A 150/180 Front plate (Aluminium)
<b>Cover colour:</b>	Smoked grey	HFP 180 Front plate hinge series
<b>Cover screws colour:</b>	Black	FP 22046 Wall fastening lug (4 pcs)
<b>Gasket material:</b>	TPE	

Temperatures:		Rating:
<b>Temperature °C (short term):</b>	-40 ... 120 °C	Ingress Protection (EN 60529): IP66/IP67
<b>Temperature °C (continuous):</b>	-40 ... 80 °C	Impact Resistance (EN 62262): IK08
<b>Temperature °F (short term):</b>	-40 ... 250 °F	Electrical insulation: Totally insulated
<b>Temperature °F (continuous):</b>	-40 ... 175 °F	Halogen free (DIN/VDE 0472, Part 815): 1
		UV resistance: UL 508
		Flammability Rating: UL 746C 5"
		Glow Wire Test (IEC 695-2-1) °C: 960
		NEMA Class: NEMA 1, 4, 4X, 6

Accessories:		Certificates:
MIV 150	Mounting plate (Galvanized steel)	SGS Fimko
		Gost R

