

Basic


NON-CONTACT DETECTION COST EFFECTIVE AND RELIABLE DETECTION OF ANY METAL PART

- Standard proximity M4, M5, M8, M12, M18, M30
- Double range (i.e. M12 4mm, M18 14mm, M30 20mm)
- Unshielded or shielded models for flush mounting
- Nickel brass or stainless steel short and long housing
- Ecolab and Diversey certifications for industrial detergents
- Multi-voltage, Metal face, Weld field immune models
- NO/NC, NPN or PNP output and programmable versions.

Detection properties

Nominal sensing distance	2 mm
--------------------------	------

Sensitivity adjustment	n/a
------------------------	-----

Application

Description	M8 short case flush mount
-------------	---------------------------

Functions	Proximity
-----------	-----------

Outputs

Output type	PNP NC 3 wires
-------------	----------------

Response time	1,000
---------------	-------

Electrical data

Operating Voltage	10-30 VDC
-------------------	-----------

Emission	≥100kHz
----------	---------

Mechanical data

Dimensions	Ø8x40
------------	-------

Connections	2 m Cable
-------------	-----------

Material	Nickel-plated brass
----------	---------------------

Generical Data

Dimensions	Ø8x40
------------	-------

Datasensing S.r.l.

Strada S.Caterina, 235
41122 Modena (MO)
Tel. 059 420411
Fax 059 253973
E-mail info@datasensing.com

date of printing

12/08/2022 14:03:41