



Motor-Protective Circuit-Breakers, 4-6, 3A, 3 p

Part no. **Z-MS-6,3/3**
 Catalog No. **248410**
 Eaton Catalog No. **Z-MS-6.3/3**



Similar to illustration

Technical data ETIM 7.0

Low-voltage industrial components (EG000017) / Motor protection circuit-breaker (EC000074)			
Electric engineering, automation, process control engineering / Low-voltage switch technology / Circuit breaker (LV < 1 kV) / Motor protection circuit-breaker (ecl@ss10.0.1-27-37-04-01 [AGZ529016])			
Overload release current setting	A	4 - 6.3	
Adjustment range undelayed short-circuit release	A	63 - 82	
With thermal protection		Yes	
Phase failure sensitive		No	
Switch off technique		Magnetic	
Rated operating voltage	V	400 - 400	
Rated permanent current Iu	A	6.3	
Rated operation power at AC-3, 230 V	kW	0	
Rated operation power at AC-3, 400 V	kW	2.2	
Type of electrical connection of main circuit		Screw connection	
Type of control element		Rocker lever	
Device construction		Complete device in housing	
With integrated auxiliary switch		No	
With integrated under voltage release		No	
Number of poles		3	
Rated short-circuit breaking capacity Icu at 400 V, AC	kA	10	
Degree of protection (IP)		IP20	
Height	mm	75	
Width	mm	54	
Depth	mm	80	