

## EK EKJB 130 T-2FSH



Sample photo

**Order symbol:** EKJB 130 T-2FSH  
**Product nbr:** 9996188  
**Description:** Enclosure, PC  
**Remarks:** Transparent hinged cover

**EAN:** 6418074053220  
**El. number:**  
**Finland:** 3435874  
**Electric No. Sweden:** 9996188

Including: Flanged Base with screws for mounting plate, cover with PUR gasket and polyamide cover screws.

| Dimensions: | Length | Width | Height |
|-------------|--------|-------|--------|
| mm:         | 280    | 190   | 130    |
| inch:       | 11.0   | 7.5   | 5.1    |

| Materials:                    |                      |
|-------------------------------|----------------------|
| <b>Material:</b>              | Polycarbonate        |
| <b>Base colour:</b>           | RAL 7035 -light grey |
| <b>Cover screws material:</b> | Polyamide            |
| <b>Cover colour:</b>          | Clear transparent    |
| <b>Cover screws colour:</b>   | Grey                 |
| <b>Gasket material:</b>       | Polyurethane         |

| Temperatures:                       |                |
|-------------------------------------|----------------|
| <b>Temperature °C (short term):</b> | -40 ... 120 °C |
| <b>Temperature °C (continuous):</b> | -40 ... 80 °C  |
| <b>Temperature °F (short term):</b> | -40 ... 250 °F |
| <b>Temperature °F (continuous):</b> | -40 ... 175 °F |

| Accessories: |          |
|--------------|----------|
| EKJB         | Base, PC |

| Accessories: |                         |
|--------------|-------------------------|
| EKJ 30-G     | Cover                   |
| EKJ 80-G     | Cover                   |
| EKJ 30-T     | Cover                   |
| EKJ 80-T     | Cover                   |
| EKJVT        | Mounting plate          |
| EKJXT        | Mounting plate isolated |
| EKV 12       | DIN-35 Mounting rail    |
| EKV 22       | DIN-35 Mounting rail    |
| EKJZR        | Extension frame         |

| Rating:                                |                                 |
|----------------------------------------|---------------------------------|
| Ingress Protection (EN 60529):         | IP65                            |
| Impact Resistance (EN 62262):          | IK08                            |
| Electrical insulation:                 | Totally insulated               |
| Halogen free (DIN/VDE 0472, Part 815): | 1                               |
| UV resistance:                         | UL 508                          |
| Flammability Rating:                   | UL 746C 5"                      |
| Glow Wire Test (IEC 695-2-1) °C:       | 960                             |
| NEMA Class:                            | NEMA 1, 3, 3S, 4, 4X, 6, 6P, 12 |

| Certificates: |  |
|---------------|--|
| Gost R        |  |

