



Sample photo

Order symbol: PC 150/125 LG
Product nbr: 6012317
Description: Enclosure, PC
Remarks: Grey cover

EAN: 6418074052155
El. number:
Finland: 3435208
Electric No. 8212027608
Denmark:
Electric No. Sweden: 6012317

Including: Base with TPE gasket, screws for mounting plate/DIN-rail and cover with polyamide cover screws.

Dimensions:			Accessories:		
mm:	180	130	125	MIN 10	DIN-15 Mounting rail
inch:	7.1	5.1	4.9	MIN 15	DIN-15 Mounting rail
			MIV 10	DIN-35 Mounting rail	
			MIV 15	DIN-35 Mounting rail	
Materials:			FP A 150/180	Front plate (Aluminium)	
Material:	Polycarbonate		HFP 180	Front plate hinge series	
Base colour:	RAL 7035 -light grey		FP 22046	Wall fastening lug (4 pcs)	
Cover screws material:	Polyamide				
Cover colour:	RAL 7035 -light grey				
Cover screws colour:	Grey				
Gasket material:	TPE				
Temperatures:					
Temperature °C (short term):	-40 ... 120 °C				
Temperature °C (continuous):	-40 ... 80 °C				
Temperature °F (short term):	-40 ... 250 °F				
Temperature °F (continuous):	-40 ... 175 °F				
Accessories:					
MIV 150	Mounting plate (Galvanized steel)				

Rating:	
Ingress Protection (EN 60529):	IP66/IP67
Impact Resistance (EN 62262):	IK08
Electrical insulation:	Totally insulated
Halogen free (DIN/VDE 0472, Part 815):	1
UV resistance:	UL 508
Flammability Rating:	UL 746C 5"
Glow Wire Test (IEC 695-2-1) °C:	960
NEMA Class:	NEMA 1, 4, 4X, 6
Certificates:	
SGS Fimko	
Gost R	

