



Data subject to change without notice. Always confirm the data is correct from the seller.

KEM 640 M3

KEM Polycarbonate 10-630A

- IP66; Enclosure types M2, M3, M4, MF11, MF01, MF02 MF03, MF04
- Self-extinguishing material
- Wide operating temperature range
- Padlockable with 3 locks
- Door interlock with defeat mechanism
- Excellent insulating properties
- Good UV resistance
- Good resistance against many chemicals
- Tested according to IEC 60947-3
- **Note!** Al-cables cannot be connected directly to switch terminals. For Al-cable connection please use a bi-metal cable connector, **available here**.

KEM 16-40 A Installation guide video
>>

KEM 63-80 A Installation guide video
>>

Technical datasheet >>

Accessories



Product details

SKU	KEM 640 M3
AC-21 400/415 V (A)	63 A
AC-21 690 V (A)	63 A
AC-22 400/415 V (A)	40 A
AC-22 690 V (A)	40 A
AC-23 400/415 V (A/kW)	40 A / 22 kW
AC-23 690 V (A/kW)	32 A / 30 kW
Cable Area to Switch Terminal (only Cu) (mm²) / Bolt size	1.5-16
Color	Standard
EAN	6419410399750
Enclosure	M3
Enclosure Type	Polycarbonate
IP Rating	66
Number of Poles	6
Operation	Front-operated
Switch type	Load Break Switch
Weight (kg)	0.9

Dimensional drawing

