

Disconnect and Fuse Terminals

Screw Type Fuse Terminals

Item no: **ASK 3 MLD**

Order no: --- --9



Torque:0,5 Nm

Electrical Ratings			
Voltage/Current/Cross-Section		- V ~ / 6.3 A / 4 mm ²	
UL		- V ~ / 10 A / AWG 26-10	
Insulation Stripping Length		12 mm	
Connection Data			
Solid Strand, Screw Connection		0,5 - 6 mm ²	
Fine Strand, Screw Connection		1,5 - 4 mm ²	
AWG Conductor		26 10	
Ordering Data		Type	Cat. No.
Polymide 6.6	Grey	ASK 3 MLD	355 210 / 355 219 (24V AC)
		ASK 3 MLD	355 220 / 355 229 (24V DC)
		ASK 3 MLD	355 310 / 355 319 (48V AC)
		ASK 3 MLD	355 320 / 355 329 (48V DC)
		ASK 3 MLD	355 510 / 355 519 (110V AC)
		ASK 3 MLD	355 520 / 355 529 (110V DC)
		ASK 3 MLD	355 610 / 355 619 (220V AC)
		ASK 3 MLD	355 620 / 355 629 (220V DC)
End Bracket			
Thickness 8 mm	MR 35 For Grey	KD 3	495 040 / 495 049
KD 3			
			
End Plate			
Thickness 1.5 mm	Polyamide 6.6	Grey	NPP ASK 3
NPP ASK 3		450 059	
			
Cross Connection			
		UK 4/10	476 239