



Klemsan®

334120 AVK 2,5/4T

2,5-4mm², screw type, single deck earth terminal block for AVK series, Insulation material PA, Yellow-Green

General Product Information	Insulating material	PA 66
	Inflammability class acc. to UL 94	V2
Dimensions	Width	6 mm
	Length	42.00 mm
	Height (MR 32)	— mm
	Height (MR 35x7.5)	44.50 mm
TSE / CE Technical Data	Nominal Voltage	— V ~
	Nominal Current	— A
	Cross Section	4 mm ²
	Norm	EN 60947-7-2
VDE Technical Data	Nominal Voltage	— V ~
	Nominal Current	— A
	Cross Section	4 mm ²
	VDE Norm	EN 60947-7-1/EN 60947-7-2
UL / CSA Technical Data	Nominal Voltage	— V ~
	Nominal Current	— A
	Cross Section	4
Connection Data	Minimum solid strand cross section	0.5 mm ²
	Maximum solid Strand cross section	6 mm ²
	Minimum fine Strand cross section	0.5 mm ²
	Maximum fine strand cross section	6 mm ²
	AWG Conductor Range	20-10
	Connection Type	screw/vidali

Insulation Stripping length

10 mm

Tightening torque

0.5/0.8 Nm



ATOM - ATOM Certificate

ATOM - ATOM Certificate

Ukrayna Uygunluk Sertifikası - Ukrayna Uygunluk Sertifikası

Ukrayna Uygunluk Sertifikası - Ukrayna Uygunluk Sertifikası

Avrupa standartlarına uygunluk belgesi - CE Certificate

Avrupa standartlarına uygunluk belgesi - CE Certificate

UL Sertifikası - UL Certificate

Norveç onaylı denizcilik sektöründe kullanılabilirlik belgesi - DNV Certificate

EAC - Russian EAC

Order Info

334120 2,5-4mm²,screw type,single deck earth terminal block for AVK series,Insulation material PA,Yellow-Green

© 2018 Klemsan A.Ş.
www.klemsan.com