




**Auxiliary contact, for PLS, postal Code, PKNM, ZP-A40, ZP-ASA, Z-MS, 2W, 0.5HP**

**Part no.** ZP-NHK  
**Catalog No.** 248437  
**EL-Nummer (Norway)** 0001609489

## Delivery program

Basic function	Accessories for combined residual-current/power circuit-breakers
Basic function accessories	Accessories for miniature circuit-breaker
Application	Tripping signal contacts
Product range	Switchgear for industrial and advanced commercial applications
Side mounting	Accessory
Contact sequence	for fitting on left to: LS, FI/LS
	

## Design verification as per IEC/EN 61439

Technical data for design verification			
Operating ambient temperature min.	°C	-5	
Operating ambient temperature max.	°C	40	

## Technical data ETIM 7.0

Devices for distribution board-/surface mounting (EG000062) / Auxiliary device for distribution board devices (EC001286)		
Electric engineering, automation, process control engineering / Electrical installation, device / Breaker switch component / Auxiliary contact unit for distribution board (ecl:ss10.0.1-27-14-35-02 [AKE327013])		
Device fitting		Universal
Additional equipment		Signalling switch
Attached at delivery		No
Assembly width (TE)		0.5
Number of contacts as normally open contact		0
Number of contacts as normally closed contact		0
Number of contacts as change-over contact		2
Number of fault-signal switches		0
Rated switch current	A	4
Rated voltage	V	250
Voltage type for actuating		AC
With auto test for earth leakage function		No
Suitable for max. number of poles main contact unit (total)		2
Suitable for max. current main contact unit	A	4

## Dimensions

