

# DATASHEET - M22-XCK1



## Label for 4-position switch, blank

**Part no.** M22-XCK1  
**279434**  
**EL Number** 4355461  
**(Norway)**

General specifications	
Product name	Eaton Moeller® series M22 Accessory Label for 4-position switch
Part no.	M22-XCK1
EAN	4015082794347
Product Length/Depth	50 millimetre
Product height	2 millimetre
Product width	50 millimetre
Product weight	0.004 kilogram
Certifications	DNV GL LR IEC/EN 60947 VDE 0660 UL/CSA certification not required VDE EN 60947 IEC 60947
Product Tradename	M22
Product Type	Accessory
Product Sub Type	Label for 4-position switch
Features & Functions	
Color	Silver
Inscription	Other
Language	Other
RAL-number	1004
Shape	Square
General information	
Degree of protection	IP66
Used with	M22S-WRJ... M22S-WJ... M22-WRJ... M22-WJ... M22-DI4... M22-D4... Four-position switch
Ambient conditions, mechanical	
Mounting position	As required
Climatic environmental conditions	
Ambient operating temperature - min	-25 °C
Ambient operating temperature - max	70 °C
Climatic proofing	Damp heat, constant, to IEC 60068-2-78 Damp heat, cyclic, to IEC 60068-2-30
Communication	
Connection to SmartWire-DT	No
Design verification	
Equipment heat dissipation, current-dependent P <sub>vid</sub>	0 W
Heat dissipation capacity P <sub>diss</sub>	0 W
Heat dissipation per pole, current-dependent P <sub>vid</sub>	0 W
Rated operational current for specified heat dissipation (I <sub>n</sub> )	0 A
Static heat dissipation, non-current-dependent P <sub>vs</sub>	0 W
10.2.2 Corrosion resistance	Meets the product standard's requirements.
10.2.3.1 Verification of thermal stability of enclosures	Meets the product standard's requirements.
10.2.3.2 Verification of resistance of insulating materials to normal heat	Meets the product standard's requirements.

10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects			Meets the product standard's requirements.
10.2.4 Resistance to ultra-violet (UV) radiation			Please enquire
10.2.5 Lifting			Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 Mechanical impact			Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 Inscriptions			Meets the product standard's requirements.
10.3 Degree of protection of assemblies			Does not apply, since the entire switchgear needs to be evaluated.
10.4 Clearances and creepage distances			Meets the product standard's requirements.
10.5 Protection against electric shock			Does not apply, since the entire switchgear needs to be evaluated.
10.6 Incorporation of switching devices and components			Does not apply, since the entire switchgear needs to be evaluated.
10.7 Internal electrical circuits and connections			Is the panel builder's responsibility.
10.8 Connections for external conductors			Is the panel builder's responsibility.
10.9.2 Power-frequency electric strength			Is the panel builder's responsibility.
10.9.3 Impulse withstand voltage			Is the panel builder's responsibility.
10.9.4 Testing of enclosures made of insulating material			Is the panel builder's responsibility.
10.10 Temperature rise			Not applicable.
10.11 Short-circuit rating			Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 Electromagnetic compatibility			Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 Mechanical function			The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

## Technical data ETIM 9.0

Low-voltage industrial components (EG000017) / Text plate for command devices (EC000624)			
Electric engineering, automation, process control engineering / Low-voltage switch technology / Command and alarm device / Identification plate for command devices (ecl@ss13-27-37-12-25 [AKF043019])			
Literal imprint			Other
Language of the imprint			Other
Imprint ISO symbols			Symbol "Arrow"
Colour			Silver
Shape			Square
Width		mm	50
Height		mm	2
Outer diameter		mm	0