



**Label for 4-position switch, blank**

**Part no.** M22-XCK2  
**279435**  
**EL Number** 4355462  
**(Norway)**

<b>General specifications</b>	
Product name	Eaton Moeller® series M22 Accessory Label for 4-position switch
Part no.	M22-XCK2
EAN	4015082794354
Product Length/Depth	50 millimetre
Product height	2 millimetre
Product width	50 millimetre
Product weight	0.004 kilogram
Certifications	LR DNV GL VDE 0660 UL/GSA certification not required IEC/EN 60947
Product Tradename	M22
Product Type	Accessory
Product Sub Type	Label for 4-position switch
<b>Features &amp; Functions</b>	
Color	Silver
Inscription	Other
Language	Other
RAL-number	1004
Shape	Square
<b>General information</b>	
Degree of protection	IP66
Used with	M22S-WRJ... M22S-WJ... M22-WRJ... M22-WJ... M22-DI4... M22-D4... 4 way selector switch actuators
<b>Ambient conditions, mechanical</b>	
Mounting position	As required
<b>Climatic environmental conditions</b>	
Ambient operating temperature - min	-25 °C
Ambient operating temperature - max	70 °C
Climatic proofing	Damp heat, constant, to IEC 60068-2-78 Damp heat, cyclic, to IEC 60068-2-30
<b>Communication</b>	
Connection to SmartWire-DT	No
<b>Design verification</b>	
Equipment heat dissipation, current-dependent Pvid	0 W
Heat dissipation capacity Pdis	0 W
Heat dissipation per pole, current-dependent Pvid	0 W
Rated operational current for specified heat dissipation (In)	0 A
Static heat dissipation, non-current-dependent Pvs	0 W
10.2.2 Corrosion resistance	Meets the product standard's requirements.
10.2.3.1 Verification of thermal stability of enclosures	Meets the product standard's requirements.
10.2.3.2 Verification of resistance of insulating materials to normal heat	Meets the product standard's requirements.
10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects	Meets the product standard's requirements.
10.2.4 Resistance to ultra-violet (UV) radiation	Please enquire

10.2.5 Lifting			Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 Mechanical impact			Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 Inscriptions			Meets the product standard's requirements.
10.3 Degree of protection of assemblies			Does not apply, since the entire switchgear needs to be evaluated.
10.4 Clearances and creepage distances			Meets the product standard's requirements.
10.5 Protection against electric shock			Does not apply, since the entire switchgear needs to be evaluated.
10.6 Incorporation of switching devices and components			Does not apply, since the entire switchgear needs to be evaluated.
10.7 Internal electrical circuits and connections			Is the panel builder's responsibility.
10.8 Connections for external conductors			Is the panel builder's responsibility.
10.9.2 Power-frequency electric strength			Is the panel builder's responsibility.
10.9.3 Impulse withstand voltage			Is the panel builder's responsibility.
10.9.4 Testing of enclosures made of insulating material			Is the panel builder's responsibility.
10.10 Temperature rise			Not applicable.
10.11 Short-circuit rating			Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 Electromagnetic compatibility			Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 Mechanical function			The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

## Technical data ETIM 9.0

Low-voltage industrial components (EG000017) / Text plate for command devices (EC000624)			
Electric engineering, automation, process control engineering / Low-voltage switch technology / Command and alarm device / Identification plate for command devices (ecl@ss13-27-37-12-25 [AKF043019])			
Literal imprint			Other
Language of the imprint			Other
Imprint ISO symbols			Symbol "Arrow"
Colour			Silver
Shape			Square
Width		mm	50
Height		mm	2
Outer diameter		mm	0