



**Label, emergency switching off, yellow, HxW=50x50mm, 4 languages, DE, EN, FR, IT**

**Part no.** **M22-XYK1**  
**216484**  
**EL Number** **4315294**  
**(Norway)**

#### General specifications

Product name	Eaton Moeller® series M22 Accessory Emergency-Stop label
Part no.	M22-XYK1
EAN	4015082164843
Product Length/Depth	50 millimetre
Product height	1 millimetre
Product width	50 millimetre
Product weight	0.003 kilogram
Certifications	DNV GL LR UL/CSA certification not required
Product Tradename	M22
Product Type	Accessory
Product Sub Type	Emergency-Stop label

#### Features & Functions

Color	Yellow
Inscription	Other
Language	Several
RAL-number	1004
Shape	Square

#### General information

Degree of protection	IP66
Size	50 x 50 mm

#### Climatic environmental conditions

Ambient operating temperature - min	-25 °C
Ambient operating temperature - max	70 °C

#### Communication

Connection to SmartWire-DT	No
----------------------------	----

#### Design verification

Equipment heat dissipation, current-dependent Pvid	0 W
Heat dissipation capacity Pdiss	0 W
Heat dissipation per pole, current-dependent Pvid	0 W
Rated operational current for specified heat dissipation (In)	0 A
Static heat dissipation, non-current-dependent Pvs	0 W
10.2.2 Corrosion resistance	Meets the product standard's requirements.
10.2.3.1 Verification of thermal stability of enclosures	Meets the product standard's requirements.
10.2.3.2 Verification of resistance of insulating materials to normal heat	Meets the product standard's requirements.
10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects	Meets the product standard's requirements.
10.2.4 Resistance to ultra-violet (UV) radiation	Please enquire
10.2.5 Lifting	Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 Mechanical impact	Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 Inscriptions	Meets the product standard's requirements.
10.3 Degree of protection of assemblies	Does not apply, since the entire switchgear needs to be evaluated.
10.4 Clearances and creepage distances	Meets the product standard's requirements.
10.5 Protection against electric shock	Does not apply, since the entire switchgear needs to be evaluated.
10.6 Incorporation of switching devices and components	Does not apply, since the entire switchgear needs to be evaluated.

10.7 Internal electrical circuits and connections		Is the panel builder's responsibility.
10.8 Connections for external conductors		Is the panel builder's responsibility.
10.9.2 Power-frequency electric strength		Is the panel builder's responsibility.
10.9.3 Impulse withstand voltage		Is the panel builder's responsibility.
10.9.4 Testing of enclosures made of insulating material		Is the panel builder's responsibility.
10.10 Temperature rise		Not applicable.
10.11 Short-circuit rating		Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 Electromagnetic compatibility		Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 Mechanical function		The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

## Technical data ETIM 9.0

Low-voltage industrial components (EG000017) / Text plate for command devices (EC000624)

Electric engineering, automation, process control engineering / Low-voltage switch technology / Command and alarm device / Identification plate for command devices (ecl@ss13-27-37-12-25 [AKF043019])

Literal imprint		Other
Language of the imprint		Several
Imprint ISO symbols		None
Colour		Yellow
Shape		Square
Width	mm	50
Height	mm	1
Outer diameter	mm	0