



On-Off switch, 2 pole, 20 A, 90 °, rear mounting, Basic switch

**Part no.** T0-1-102/XZ  
**Catalog No.** 005736

**EL-Nummer (Norway)** 0001456651

Similar to illustration

### Delivery program

|   |       |                 |  |
|---|-------|-----------------|--|
| Product range                             |       |                 | On-Off switch  |
| Part group reference                      |       |                 | T0   |
| Number of poles                           |       |                 | 2 pole   |
| Design                                    |       |                 | rear mounting<br>Basic switch  |
| Contact sequence                          |       |                 | <br>   |
| Switching angle                           |       | °               | 90   |
| Front plate no.                           |       |                 | <br><b>FS 908</b>  |
| <b>Motor rating AC-23A, 50 - 60 Hz</b>    |       |                 |  |
| 400 V                                     | P     | kW              | 5.5  |
| Rated uninterrupted current               | $I_u$ | A               | 20   |
| Note on rated uninterrupted current $I_u$ |       |                 | Rated uninterrupted current $I_u$ is specified for max. cross-section. |
| Number of contact units                   |       | contact unit(s) | 1  |

### Technical data

#### General

|                                       |           |      |   |
|---------------------------------------|-----------|------|---|
| Standards                             |           |      | IEC/EN 60947, VDE 0660, IEC/EN 60204<br>Switch-disconnector according to IEC/EN 60947-3 |
| Climatic proofing                     |           |      | Damp heat, constant, to IEC 60068-2-78<br>Damp heat, cyclic, to IEC 60068-2-30          |
| Ambient temperature                   |           |      |   |
| Open                                  |           | °C   | -25 - +50   |
| Enclosed                              |           | °C   | -25 - +40   |
| Overvoltage category/pollution degree |           |      | III/3   |
| Rated impulse withstand voltage       | $U_{imp}$ | V AC | 6000  |
| Mechanical shock resistance           |           | g    | 15  |
| Mounting position                     |           |      | As required   |

#### Contacts

|   |       |      |  |
|---|-------|------|--|
| Mechanical variables                      |       |      |  |
| Number of poles                           |       |      | 2 pole   |
| Electrical characteristics                |       |      |  |
| Rated operational voltage                 | $U_e$ | V AC | 690  |
| Rated uninterrupted current               | $I_u$ | A    | 20   |
| Note on rated uninterrupted current $I_u$ |       |      | Rated uninterrupted current $I_u$ is specified for max. cross-section. |

|  |                 |                  |                                |
|--|-----------------|------------------|--------------------------------|
| Load rating with intermittent operation, class 12          |                 |                  |                                |
| AB 25 % DF   |                 | x I <sub>e</sub> | 2                              |
| AB 40 % DF   |                 | x I <sub>e</sub> | 1.6                            |
| AB 60 % DF   |                 | x I <sub>e</sub> | 1.3                            |
| Short-circuit rating                                       |                 |                  |                                |
| Fuse   |                 | A gG/gL          | 20                             |
| Rated short-time withstand current (1 s current)           | I <sub>cw</sub> | A <sub>rms</sub> | 320                            |
| Note on rated short-time withstand current I <sub>cw</sub> |                 |                  | Current for a time of 1 second |
| Rated conditional short-circuit current                    | I <sub>q</sub>  | kA               | 6                              |

### Switching capacity

|   |                |                   |       |
|---|----------------|-------------------|-------|
| cos φ rated making capacity as per IEC 60947-3                          |                | A                 | 130   |
| Rated breaking capacity cos φ to IEC 60947-3                            |                |                   |       |
| 230 V   |                | A                 | 100   |
| 400/415 V   |                | A                 | 110   |
| 500 V   |                | A                 | 80    |
| 690 V   |                | A                 | 60    |
| Safe isolation to EN 61140  |                |                   |       |
| between the contacts  |                | V AC              | 440   |
| Current heat loss per contact at I <sub>e</sub>                         |                | W                 | 0.6   |
| Current heat loss per auxiliary circuit at I <sub>e</sub> (AC-15/230 V) |                | CO                | 0.6   |
| Lifespan, mechanical  | Operations     | x 10 <sup>6</sup> | > 0.4 |
| Maximum operating frequency   | Operations/h   |                   | 1200  |
| AC  |                |                   |       |
| AC-3  |                |                   |       |
| Rating, motor load switch   | P              | kW                |       |
| 220 V 230 V   | P              | kW                | 3     |
| 230 V Star-delta  | P              | kW                | 5.5   |
| 400 V 415 V   | P              | kW                | 5.5   |
| 400 V Star-delta  | P              | kW                | 7.5   |
| 500 V   | P              | kW                | 5.5   |
| 500 V Star-delta  | P              | kW                | 7.5   |
| 690 V   | P              | kW                | 4     |
| 690 V Star-delta  | P              | kW                | 5.5   |
| Rated operational current motor load switch                             |                |                   |       |
| 230 V   | I <sub>e</sub> | A                 | 11.5  |
| 230 V star-delta  | I <sub>e</sub> | A                 | 20    |
| 400V 415 V  | I <sub>e</sub> | A                 | 11.5  |
| 400 V star-delta  | I <sub>e</sub> | A                 | 20    |
| 500 V   | I <sub>e</sub> | A                 | 9     |
| 500 V star-delta  | I <sub>e</sub> | A                 | 15.6  |
| 690 V   | I <sub>e</sub> | A                 | 4.9   |
| 690 V star-delta  | I <sub>e</sub> | A                 | 8.5   |
| AC-21A  |                |                   |       |
| Rated operational current switch  |                |                   |       |
| 440 V   | I <sub>e</sub> | A                 | 20    |
| AC-23A  |                |                   |       |
| Motor rating AC-23A, 50 - 60 Hz   |                |                   |       |
| 230 V   | P              | kW                | 3     |
| 400 V 415 V   | P              | kW                | 5.5   |
| 500 V   | P              | kW                | 7.5   |
| 690 V   | P              | kW                | 5.5   |
| Rated operational current motor load switch                             |                |                   |       |
| 230 V   | I <sub>e</sub> | A                 | 13.3  |
| 400 V 415 V   | I <sub>e</sub> | A                 | 13.3  |

|   |                   |                |   |
|---|-------------------|----------------|---|
| 500 V   | I <sub>e</sub>    | A              | 13.3  |
| 690 V   | I <sub>e</sub>    | A              | 7.6   |
| <b>DC</b>                                     |                   |                |   |
| DC-1, Load-break switches L/R = 1 ms          |                   |                |   |
| Rated operational current                     | I <sub>e</sub>    | A              | 10  |
| Voltage per contact pair in series            |                   | V              | 60  |
| DC-21A  |                   |                |   |
| Rated operational current                     | I <sub>e</sub>    | A              | 1   |
| Contacts                                      |                   | Quantity       | 1   |
| DC-23A, motor load switch L/R = 15 ms         |                   |                |   |
| 24 V  |                   |                |   |
| Rated operational current                     | I <sub>e</sub>    | A              | 10  |
| Contacts                                      |                   | Quantity       | 1   |
| 48 V  |                   |                |   |
| Rated operational current                     | I <sub>e</sub>    | A              | 10  |
| Contacts                                      |                   | Quantity       | 2   |
| 60 V  |                   |                |   |
| Rated operational current                     | I <sub>e</sub>    | A              | 10  |
| Contacts                                      |                   | Quantity       | 3   |
| 120 V   |                   |                |   |
| Rated operational current                     | I <sub>e</sub>    | A              | 5   |
| Contacts                                      |                   | Quantity       | 3   |
| 240 V   |                   |                |   |
| Rated operational current                     | I <sub>e</sub>    | A              | 5   |
| Contacts                                      |                   | Quantity       | 5   |
| DC-13, Control switches L/R = 50 ms           |                   |                |   |
| Rated operational current                     | I <sub>e</sub>    | A              | 10  |
| Voltage per contact pair in series            |                   | V              | 32  |
| Control circuit reliability at 24 V DC, 10 mA | Fault probability | H <sub>F</sub> | < 10 <sup>-5</sup> , < 1 fault in 100000 operations |

### Terminal capacities

|                                      |  |                 |                                      |
|--------------------------------------|--|-----------------|--------------------------------------|
| Solid or stranded                    |  | mm <sup>2</sup> | 1 x (1 - 2,5)<br>2 x (1 - 2,5)       |
| Flexible with ferrules to DIN 46228  |  | mm <sup>2</sup> | 1 x (0.75 - 2.5)<br>2 x (0.75 - 2.5) |
| Terminal screw                       |  |                 | M3.5                                 |
| Tightening torque for terminal screw |  | Nm              | 1                                    |

### Technical safety parameters:

|              |  |  |   |
|--------------|--|--|---|
| <b>Notes</b> |  |  | B10 <sub>q</sub> values as per EN ISO 13849-1, table C1 |
|--------------|--|--|---|

### Rating data for approved types

|                   |  |  |      |
|-------------------|--|--|------|
| Terminal capacity |  |  |      |
| Terminal screw    |  |  | M3.5 |

## Design verification as per IEC/EN 61439

|  |                   |    |  |
|--|-------------------|----|--|
| Technical data for design verification                   |                   |    |  |
| Rated operational current for specified heat dissipation | I <sub>n</sub>    | A  | 20   |
| Heat dissipation per pole, current-dependent             | P <sub>vid</sub>  | W  | 0.6  |
| Equipment heat dissipation, current-dependent            | P <sub>vid</sub>  | W  | 0  |
| Static heat dissipation, non-current-dependent           | P <sub>vs</sub>   | W  | 0  |
| Heat dissipation capacity                                | P <sub>diss</sub> | W  | 0  |
| Operating ambient temperature min.                       |                   | °C | -25  |
| Operating ambient temperature max.                       |                   | °C | 50   |
| IEC/EN 61439 design verification                         |                   |    |  |
| 10.2 Strength of materials and parts                     |                   |    |  |
| 10.2.2 Corrosion resistance                              |                   |    | Meets the product standard's requirements. |
| 10.2.3.1 Verification of thermal stability of enclosures |                   |    | Meets the product standard's requirements. |

|  |  |  |
|--|--|--|
| 10.2.3.2 Verification of resistance of insulating materials to normal heat   |  | Meets the product standard's requirements.   |
| 10.2.3.3 Verification of resistance of insulating materials to abnormal heat and fire due to internal electric effects |  | Meets the product standard's requirements.   |
| 10.2.4 Resistance to ultra-violet (UV) radiation   |  | UV resistance only in connection with protective shield.   |
| 10.2.5 Lifting   |  | Does not apply, since the entire switchgear needs to be evaluated.   |
| 10.2.6 Mechanical impact   |  | Does not apply, since the entire switchgear needs to be evaluated.   |
| 10.2.7 Inscriptions  |  | Meets the product standard's requirements.   |
| 10.3 Degree of protection of ASSEMBLIES  |  | Does not apply, since the entire switchgear needs to be evaluated.   |
| 10.4 Clearances and creepage distances   |  | Meets the product standard's requirements.   |
| 10.5 Protection against electric shock   |  | Does not apply, since the entire switchgear needs to be evaluated.   |
| 10.6 Incorporation of switching devices and components   |  | Does not apply, since the entire switchgear needs to be evaluated.   |
| 10.7 Internal electrical circuits and connections  |  | Is the panel builder's responsibility.   |
| 10.8 Connections for external conductors   |  | Is the panel builder's responsibility.   |
| 10.9 Insulation properties   |  |  |
| 10.9.2 Power-frequency electric strength   |  | Is the panel builder's responsibility.   |
| 10.9.3 Impulse withstand voltage   |  | Is the panel builder's responsibility.   |
| 10.9.4 Testing of enclosures made of insulating material   |  | Is the panel builder's responsibility.   |
| 10.10 Temperature rise   |  | The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices. |
| 10.11 Short-circuit rating   |  | Is the panel builder's responsibility. The specifications for the switchgear must be observed.                                   |
| 10.12 Electromagnetic compatibility  |  | Is the panel builder's responsibility. The specifications for the switchgear must be observed.                                   |
| 10.13 Mechanical function  |  | The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.                         |

## Technical data ETIM 7.0

Low-voltage industrial components (EG000017) / Switch disconnecter (EC000216)

Electric engineering, automation, process control engineering / Low-voltage switch technology / Off-load switch, circuit breaker, control switch / Switch disconnecter (ecl@ss10.0.1-27-37-14-03 [AKF060013])

|   |    |  |
|---|----|--|
| Version as main switch                                  |    | No                                       |
| Version as maintenance-/service switch                  |    | No                                       |
| Version as safety switch                                |    | No                                       |
| Version as emergency stop installation                  |    | No                                       |
| Version as reversing switch                             |    | No                                       |
| Number of switches                                      |    | 1  |
| Max. rated operation voltage Ue AC                      | V  | 690                                      |
| Rated operating voltage                                 | V  | 690 - 690                                |
| Rated permanent current Iu                              | A  | 20                                       |
| Rated permanent current at AC-23, 400 V                 | A  | 13.3                                     |
| Rated permanent current at AC-21, 400 V                 | A  | 20                                       |
| Rated operation power at AC-3, 400 V                    | kW | 5.5                                      |
| Rated short-time withstand current Icw                  | kA | 0.32                                     |
| Rated operation power at AC-23, 400 V                   | kW | 5.5                                      |
| Switching power at 400 V                                | kW | 5.5                                      |
| Conditioned rated short-circuit current Iq              | kA | 6  |
| Number of poles   |    | 2  |
| Number of auxiliary contacts as normally closed contact |    | 0  |
| Number of auxiliary contacts as normally open contact   |    | 0  |
| Number of auxiliary contacts as change-over contact     |    | 0  |
| Motor drive optional                                    |    | No                                       |
| Motor drive integrated                                  |    | No                                       |
| Voltage release optional                                |    | No                                       |
| Device construction                                     |    | Built-in device fixed built-in technique |
| Suitable for ground mounting                            |    | Yes                                      |
| Suitable for front mounting 4-hole                      |    | No                                       |
| Suitable for front mounting centre                      |    | No                                       |
| Suitable for distribution board installation            |    | No                                       |

|   |  |                  |
|---|--|------------------|
| Suitable for intermediate mounting            |  | Yes              |
| Colour control element                        |  | Black            |
| Type of control element                       |  | Toggle           |
| Interlockable                                 |  | No               |
| Type of electrical connection of main circuit |  | Screw connection |
| Degree of protection (IP), front side         |  | IP00             |
| Degree of protection (NEMA)                   |  | Other            |

## Additional product information (links)

|  |   |
|--|---|
| Display flip catalog page.                                   | <a href="http://ecat.moeller.net/flip-cat/?edition=K115A&amp;startpage=40">http://ecat.moeller.net/flip-cat/?edition=K115A&amp;startpage=40</a>                                     |
| Ordering form for SOND switches and SOND front plates(DE_EN) | <a href="ftp://ftp.moeller.net/DOCUMENTATION/PDF/MZ008005ZU_Orderform_Customized_Switch.pdf">ftp://ftp.moeller.net/DOCUMENTATION/PDF/MZ008005ZU_Orderform_Customized_Switch.pdf</a> |
| Ordering form for SOND switches and SOND front plates(DE_EN) | <a href="ftp://ftp.moeller.net/DOCUMENTATION/PDF/MZ008006ZU_Orderform_Customized_Switch.pdf">ftp://ftp.moeller.net/DOCUMENTATION/PDF/MZ008006ZU_Orderform_Customized_Switch.pdf</a> |