



Klemsan®

334140 AVK 6/10T

6-10mm², screw type, single deck earth terminal block for AVK series, Insulation material PA, Yellow-Green

General Product Information	Insulating material	PA 66
	Inflammability class acc. to UL 94	V2
Dimensions	Width	mm
	Length	mm
	Height (MR 32)	mm
	Height (MR 35x7.5)	mm
TSE / CE Technical Data	Nominal Voltage	— V ~
	Nominal Current	— A
	Cross Section	10 mm ²
	Norm	EN 60947-7-2
VDE Technical Data	Nominal Voltage	— V ~
	Nominal Current	— A
	Cross Section	10 mm ²
	VDE Norm	EN 60947-7-1/EN 60947-7-2
UL / CSA Technical Data	Nominal Voltage	V ~
	Nominal Current	A
	Cross Section	
Connection Data	Minimum solid strand cross section	mm ²
	Maximum solid Strand cross section	mm ²
	Minimum fine Strand cross section	mm ²
	Maximum fine strand cross section	mm ²
	AWG Conductor Range	
	Connection Type	

Insulation Stripping length

mm

Tightening torque

Nm



ATOM - ATOM Certificate

Ukrayna Uygunluk Sertifikası - Ukrayna Uygunluk Sertifikası

Avrupa standartlarına uygunluk belgesi - CE Certificate

Norveç onaylı denizcilik sektöründe kullanılabilirlik belgesi - DNV Certificate

© 2018 Klemsan A.Ş.
www.klemsan.com