

## Basic



### NON-CONTACT DETECTION COST EFFECTIVE AND RELIABLE DETECTION OF ANY METAL PART

- Standard proximity M4, M5, M8, M12, M18, M30
- Double range (i.e. M12 4mm, M18 14mm, M30 20mm)
- Unshielded or shielded models for flush mounting
- Nickel brass or stainless steel short and long housing
- Ecolab and Diversey certifications for industrial detergents
- Multi-voltage, Metal face, Weld field immune models
- NO/NC, NPN or PNP output and programmable versions.

#### Detection properties

Nominal sensing distance	2 mm
--------------------------	------

Sensitivity adjustment	n/a
------------------------	-----

#### Application

Description	M8 short case flush mount
-------------	---------------------------

Functions	Proximity
-----------	-----------

#### Outputs

Output type	PNP NO 3 wires
-------------	----------------

Response time	1,000
---------------	-------

#### Electrical data

Operating Voltage	10-30 VDC
-------------------	-----------

Emission	≥100kHz
----------	---------

#### Mechanical data

Dimensions	Ø8x40
------------	-------

Connections	2 m Cable
-------------	-----------

Material	Nickel-plated brass
----------	---------------------

#### General Data

Dimensions	Ø8x40
------------	-------

---

---

---

**Datasensing S.r.l.**

Strada S.Caterina, 235  
41122 Modena (MO)  
Tel. 059 420411  
Fax 059 253973  
E-mail [info@datasensing.com](mailto:info@datasensing.com)

**date of printing**

12/08/2022 13:58:07