



Klemsan®

304124 AVK 2,5

2,5mm²,screw type,single deck feed through terminal block,Insulation material PA,Red

General Product Information	Insulating material	PA 66
	Inflammability class acc. to UL 94	V2
Dimensions	Width	5 mm
	Length	44.2 mm
	Height (MR 32)	— mm
	Height (MR 35x7.5)	44.5 mm
TSE / CE Technical Data	Nominal Voltage	750 V ~
	Nominal Current	24 A
	Cross Section	2.5 mm ²
	Norm	EN 60947-7-1
VDE Technical Data	Nominal Voltage	750 V ~
	Nominal Current	24 A
	Cross Section	2.5 mm ²
	VDE Norm	IEC 60947-7-1
UL / CSA Technical Data	Nominal Voltage	600 V ~
	Nominal Current	20 A
	Cross Section	AWG/26-12
ATEX Technical Data	Nominal Voltage	630 V ~
	Nominal Current	21 A
	Cross Section	2.5
Connection Data	Minimum solid strand cross section	0.5 mm ²
	Maximum solid Strand cross section	4 mm ²
	Minimum fine Strand cross section	1.5 mm ²

Maximum fine strand cross section	2.5 mm ²
AWG Conductor Range	26-12
Connection Type	screw/vidalı
Insulation Stripping length	10 mm
Tightening torque	0.4 Nm



Alçak Gerilim direktiflerine uygunluk belgesi - VDE Certificate

ATOM - ATOM Certificate

Türk Standartlarına Uygunluk Belgesi - TSE Certificate

Ukrayna Uygunluk Sertifikası - Ukrayna Uygunluk Sertifikası

Avrupa standartlarına uygunluk belgesi - CE Certificate

UL Sertifikası - UL Certificate

CSA - CE Certificate

Norveç onaylı denizcilik sektöründe kullanılabilirlik belgesi - DNV Certificate

Rusya Onaylı Denizcilik Sertifikası - Rusya Denizcilik Certificate

Order Info

■	304120	2,5mm ² ,screw type,single deck feed through terminal block,Insulation material PA,Grey
■	304121	2,5mm ² ,screw type,single deck feed through terminal block,Insulation material PA,Blue
■	304122	2,5mm ² ,screw type,single deck feed through terminal block,Insulation material PA,Green
■	304123	2,5mm ² ,screw type,single deck feed through terminal block,Insulation material PA,Yellow
■	304124	2,5mm ² ,screw type,single deck feed through terminal block,Insulation material PA,Red
■	304129	2,5mm ² ,screw type,single deck feed through terminal block,Insulation material PA,Beige
■	304125	2,5mm ² ,screw type,single deck feed through terminal block,Insulation material PA,Black
□	304126	2,5mm ² ,screw type,single deck feed through terminal block,Insulation material PA,White
■	304127	2,5mm ² ,screw type,single deck feed through terminal block,Insulation material PA,Orange
■	304128	2,5mm ² ,screw type,single deck feed through terminal block,Insulation material PA,Brown

