

ODE-3-240095-3F42

Optidrive E3 VFD Datasheet

4 kW, 9.5 A, 380-480 V, 3PH,
 IP20 Variable Frequency Drive
 with EMC Filter

Input Ratings

Supply Voltage	380-480 V
Input Phases	3
Supply Current Continuous	11.5 A
Supply Fuse or MCB (Type B)	16 A

Output Ratings

Motor Output Rating	4 kW
Output Voltage	0 – Supply Voltage
Output Current	9.5 A

Cable Information

Max Supply Cable Size	8 mm ²
Max Motor Cable Size	8 mm ²
Max motor cable length	100 m

Factory Build Options


EMC Filter	Internal EMC Filter
Brake Transistor	Internal Brake Transistor
Enclosure	IP20

Installation Options & Peripherals

- ▶ Braking Resistors
- ▶ Communication Interfaces
- ▶ EMC Filters
- ▶ I/O Options
- ▶ Input Chokes
- ▶ Optistick Smart
- ▶ Output Filters
- ▶ Remote Keypads
- ▶ RJ45 Accessories
- ▶ USB PC Connection Kit



Dimensions



Size	2
Height	221 mm
Width	110 mm
Depth	150 mm
Weight	1.7 kg
Packaged Weight	1.83 kg

This website uses cookies to ensure you get the best experience - by using this website, you are agreeing to