

## Terminal shroud, 3p, for switch-disconnector P3

Part no. H-P3

021999 1456532

EL Number

(Norway)

Product name
Part no.  EAN 401500219996 Product Length/Opth 105 millimetre Product height Product height 40 millimetre Product weight 41 millimetre Product weight Certifications Product Tradename None Product Tradename None Product Trype Accessory Product Sub Type Terminal shroud General information Accessories Accessory/spare part type Type Tover Terminal shroud Cover Type Terminal cover Climatic environmental conditions Ambient operating temperature - min Ambient operating temperature - min Ambient operating temperature - max Sor C Design verification Equipment heat dissipation, current-dependent Pvid Heat dissipation capacity Pdiss Heat dissipation, current-dependent Pvid Neat dissipation, current-dependent Pvid Neat does not apply a product standard's requirements. Design verification of resistance of insulating materials to normal heat 102.31 Verification of resistance of insulating materials to normal heat 102.31 Verification of resistance of insulating materials to normal heat 102.42 Resistance to ultra-violet (UV) radiation 102.51 Lifting Dees not apply, since the entire swritchgear needs to be evaluated. 102.51 Lifting Dees not apply, since the entire swritchgear needs to be evaluated.
EAN Product Length/Depth Product Length/Depth Product Length/Depth Product height 40 millimetre Product width Product width Product weight 0.005 kilogram Carifications UUCSA certification not required Product Tradename Product Tradename Product Type Accessory Product Type Product Sub Type Terminal shroud  Ceneral information  Accessories Accessories Accessory Town Terminal shroud  Ceneral information  Accessory Town Terminal cover  Climatic environmental conditions  Ambient operating temperature - min Ambient operating temperature - max 50 °C  Design verification Equipment heat dissipation, current-dependent Pvid Heat dissipation capacity Pdiss 0 W Rated operational current for specified heat dissignation (In) Static heat dissipation, non-current-dependent Pvs 10.2.2 Corrosion resistance 10.2.3 (Perification of resistance of insulating materials to normal heat 10.2.3 (Perification of resistance of insulating materials to normal heat 10.2.3 (Perification of resistance of insulating materials to normal heat 10.2.3 (Perification of resistance of insulating materials to normal heat 10.2.3 (Perification of resistance of insulating materials to normal heat 10.2.3 (Perification of resistance of insulating materials to normal heat 10.2.4 (Peristance to ultra-violet (UV) radiation 10.2.5 (Uting) 10.
Product Length/Depth Product height Product weight Product weight Product weight Product weight Product weight Product registrations UL/CSA certification not required UL/CSA certification not required Product Tradename None Product Tradename None Product Sub Type Accessory Product Sub Type Remarks of Cover Product Sub Type Cover Terminal shroud Ceneral information Accessories Shroud for connection terminals for (busbar tag shroud) Accessories Cover Type Terminal cover Climatic environmental conditions Ambient operating temperature - min Abbient operating temperature - max Sor C  Design verification Equipment heat dissipation, current-dependent Pvid Heat dissipation capacity Pdiss Heat dissipation per pole, current-dependent Pvid Rated operational current for specified heat dissipation (In) Static heat dissipation, non-current-dependent Pvs DU2.2 Corrosion resistance DU2.3 I Verification of thermal stability of enclosures Meets the product standard's requirements. DU2.4 Resistance to ultra-violat (UV) radiation Meets the product standard's requirements. DU2.4 Resistance to ultra-violat (UV) radiation Does not apply, since the entire switchgear needs to be evaluated. Does not apply, since the entire switchgear needs to be evaluated.
Product height Product weight Quas kilogram Certifications UUCSA certification not required Product Tradename Product Tradename Product Tradename Product Trype Accessory Product Sub Type Terminal shroud General information Accessories Accessories Accessory Type Terminal shroud General information Accessory Type Terminal cover Climatic environmental conditions Ambient operating temperature - min Ambient operating temperature - min Ambient operating temperature - max So "C  Design verification Equipment heat dissipation, current-dependent Pvid Heat dissipation capacity Pdiss Heat dissipation non-current-dependent Pvid No Rated operational current for specified heat dissipation (In) Ox Static heat dissipation of non-current-dependent Pvs Neets the product standard's requirements.
Product width Product weight Octrifications UL/CSA certification not required Product Tradename Product Trype Product Trype Accessory Product Sub Type General information Accessories Accessoryspare part type Type Terminal shroud Cover Type Terminal cover Climatic environmental conditions Ambient operating temperature - min Ambient operating temperature - max So °C  Design verification Equipment heat dissipation, current-dependent Pvid Heat dissipation capacity Pdiss Heat dissipation non-current-dependent Pvid Nated operational current for specified heat dissipation (In) State heat dissipation, non-current-dependent Pvs Now Rated operational current for specified heat dissipation (In) State heat dissipation of resistance 10.2.3.1 Verification of resistance of insulating materials to normal heat 10.2.3.2 Resistance to ultra-violet (UV) radiation Meets the product standard's requirements. 10.2.4 Resistance to ultra-violet (UV) radiation Meets the product standard's requirements. 10.2.5 Lifting Does not apply, since the entire switchgear needs to be evaluated.
Product weight Certifications UL/CSA certification not required UL/CSA certification not required None Product Type Product Sub Type Product Sub Type Product Sub Type Received information Accessories Accessories Accessory Product Guntarian Accessories Accessory Shroud for connection terminals for (busbar tag shroud) Cover Type Terminal cover Climatic environmental conditions Ambient operating temperature - min Ambient operating temperature - max Design verification Equipment heat dissipation, current-dependent Pvid Heat dissipation capacity Pdiss Heat dissipation per pole, current-dependent Pvid Heat dissipation per pole, current-dependent Pvid Astatic heat dissipation, non-current-dependent Pvi Design verification  Equipment heat dissipation of resistance of insulating materials to normal heat Meets the product standard's requirements.  10.2.2 Corrosion resistance Meets the product standard's requirements.  10.2.3 Verification of thermal stability of enclosures Meets the product standard's requirements.  10.2.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects Meets the product standard's requirements.  10.2.5 Lifting Does not apply, since the entire switchgear needs to be evaluated.
Certifications  Product Tradename Product Type Product Sub Type Product Sub Type  Ceneral information  Accessories Accessories Accessory Terminal shroud  Cover Type Terminal cover  Climatic environmental conditions  Ambient operating temperature - min Ambient operating temperature - max  Design verification  Equipment heat dissipation, current-dependent Pvid Heat dissipation capacity Pdiss Heat dissipation or per pole, current-dependent Pvid Rated operational current for specified heat dissipation (In) Static heat dissipation, on-current-dependent Pvs  10.2.3 L'varification of thermal stability of enclosures  10.2.3.1 Varification of thermal stability of enclosures  10.2.3 Resists of insul. mat to abnormal heat/fire by internal elect. effects  10.2.5 Lifting  Does not apply, since the entire switchgear needs to be evaluated.
Product Type Product Type Product Sub Type  General information  Accessories Accessories Accessory Type Terminal shroud  Cover Type Type Terminal cover  Climatic environmental conditions Ambient operating temperature - min Ambient operating temperature - max  Design verification  Equipment heat dissipation, current-dependent Pvid Heat dissipation capacity Pdiss Heat dissipation per pole, current-dependent Pvid Heat dissipation on per pole, current-dependent Pvid Nated operational current for specified heat dissipation (In) Static heat dissipation, non-current-dependent Pvs  10.2.2 Corrosion resistance Meets the product standard's requirements.  10.2.3 Verification of thermal stability of enclosures Meets the product standard's requirements.  10.2.3 Resist of insul. mat. to abnormal heat/fire by internal elect. effects Meets the product standard's requirements.
Product Type Product Sub Type  General information  Accessories Accessory  Accessory  Shroud for connection terminals for (busbar tag shroud)  Cover  Type Terminal cover  Climatic environmental conditions  Ambient operating temperature - min Ambient operating temperature - max  So °C  Design verification  Equipment heat dissipation, current-dependent Pvid Heat dissipation capacity Pdiss Heat dissipation per pole, current-dependent Pvid  Rated operational current for specified heat dissipation (In) Static heat dissipation, non-current-dependent Pvs  10.2.2 Corrosion resistance  Meets the product standard's requirements.  10.2.3.1 Verification of thermal stability of enclosures  10.2.3.2 Verification of resistance of insulating materials to normal heat  10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects  10.2.4 Resistance to ultra-violet (UV) radiation  10.2.5 Lifting  Does not apply, since the entire switchgear needs to be evaluated.
Product Sub Type  General information  Accessories  Accessory/spare part type  Type  Cover  Type  Climatic environmental conditions  Ambient operating temperature - min Ambient operating temperature - max  So °C  Design verification  Equipment heat dissipation, current-dependent Pvid Heat dissipation capacity Pdiss Heat dissipation per pole, current-dependent Pvid  Rated operational current for specified heat dissipation (In)  Static heat dissipation, non-current-dependent Pvs  10.2.2 Corrosion resistance  Meets the product standard's requirements.  10.2.3.1 Verification of fresistance of insulating materials to normal heat  10.2.3.2 Verification of resistance to ultra-violet (UV) radiation  10.2.5 Lifting  Terminal shroud  Shroud for connection terminals for (busbar tag shroud)  Cover  Terminal cover  Terminal cover  Terminal shroud  Shroud for connection terminals for (busbar tag shroud)  Cover  Terminal cover  Terminal cover  Terminal stover  Terminal stover  Terminal stover  Terminal cover  Terminal cov
General information  Accessory/spare part type Type Cover Type Terminal cover  Climatic environmental conditions Abbient operating temperature - min Ambient operating temperature - max 50 °C  Design verification Equipment heat dissipation, current-dependent Pvid Heat dissipation capacity Pdiss Heat dissipation prole, current-dependent Pvid Rated operational current for specified heat dissipation (In) Static heat dissipation, non-current-dependent Pvs  10.2.2 Corrosion resistance Meets the product standard's requirements. 10.2.3.1 Verification of thermal stability of enclosures Meets the product standard's requirements. 10.2.3.2 Verification of resistance of insulating materials to normal heat Meets the product standard's requirements. Does not apply, since the entire switchgear needs to be evaluated.
Accessory/spare part type Type Tcover  Type Climatic environmental conditions  Ambient operating temperature - min Ambient operating temperature - max 50 °C  Design verification Equipment heat dissipation, current-dependent Pvid Heat dissipation capacity Pdiss Heat dissipation propel, current-dependent Pvid 0 W Rated operational current for specified heat dissipation (In) Static heat dissipation, non-current-dependent Pvs 0 W  10.2.2 Corrosion resistance Meets the product standard's requirements. 10.2.3.1 Verification of thermal stability of enclosures 10.2.3.2 Verification of resistance of insulating materials to normal heat 10.2.3.3 Resist, of insul. mat. to abnormal heat/fire by internal elect. effects Meets the product standard's requirements. Des not apply, since the entire switchgear needs to be evaluated.
Accessory/spare part type Type Terminal cover  Climatic environmental conditions  Ambient operating temperature - min Ambient operating temperature - max 50 °C  Design verification  Equipment heat dissipation, current-dependent Pvid 0 W Heat dissipation capacity Pdiss 0 W Heat dissipation per pole, current-dependent Pvid 0 W Rated operational current for specified heat dissipation (In) Static heat dissipation, non-current-dependent Pvs 0 W  10.22 Corrosion resistance Meets the product standard's requirements. 102.3.1 Verification of thermal stability of enclosures Meets the product standard's requirements. 102.3.2 Verification of resistance of insulating materials to normal heat 102.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects Meets the product standard's requirements. 102.4 Resistance to ultra-violet (UV) radiation Meets the product standard's requirements. 102.5 Lifting Does not apply, since the entire switchgear needs to be evaluated.
Type  Climatic environmental conditions  Ambient operating temperature - min  Ambient operating temperature - max  50 °C  Design verification  Equipment heat dissipation, current-dependent Pvid  Heat dissipation capacity Pdiss  Heat dissipation per pole, current-dependent Pvid  Rated operational current for specified heat dissipation (In)  Static heat dissipation, non-current-dependent Pvs  10.2.2 Corrosion resistance  Meets the product standard's requirements.  10.2.3.1 Verification of thermal stability of enclosures  Meets the product standard's requirements.  Does not apply, since the entire switchgear needs to be evaluated.
Climatic environmental conditions  Ambient operating temperature - min  Ambient operating temperature - max  50 °C  Design verification  Equipment heat dissipation, current-dependent Pvid  Heat dissipation capacity Pdiss  Heat dissipation per pole, current-dependent Pvid  OW  Rated operational current for specified heat dissipation (In)  Static heat dissipation, non-current-dependent Pvs  OW  10.2.2 Corrosion resistance  Meets the product standard's requirements.  10.2.3.1 Verification of thermal stability of enclosures  Meets the product standard's requirements.  10.2.3.2 Verification of resistance of insulating materials to normal heat  10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects  Meets the product standard's requirements.  10.2.4 Resistance to ultra-violet (UV) radiation  Meets the product standard's requirements.  Does not apply, since the entire switchgear needs to be evaluated.
Ambient operating temperature - min  Ambient operating temperature - max  50 °C  Design verification  Equipment heat dissipation, current-dependent Pvid  Heat dissipation capacity Pdiss  0 W  Heat dissipation per pole, current-dependent Pvid  0 W  Rated operational current for specified heat dissipation (In)  Static heat dissipation, non-current-dependent Pvs  10.2.2 Corrosion resistance  Meets the product standard's requirements.  10.2.3.1 Verification of thermal stability of enclosures  10.2.3.2 Verification of resistance of insulating materials to normal heat  10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects  10.2.4 Resistance to ultra-violet (UV) radiation  Does not apply, since the entire switchgear needs to be evaluated.
Ambient operating temperature - max  Design verification  Equipment heat dissipation, current-dependent Pvid  Heat dissipation capacity Pdiss  Heat dissipation per pole, current-dependent Pvid  Rated operational current for specified heat dissipation (In)  Static heat dissipation, non-current-dependent Pvs  10.22 Corrosion resistance  Meets the product standard's requirements.  10.2.3.1 Verification of thermal stability of enclosures  Meets the product standard's requirements.  10.2.3.2 Verification of resistance of insulating materials to normal heat  10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects  10.2.4 Resistance to ultra-violet (UV) radiation  10.2.5 Lifting  50 °C  0 W  Meets the product standard is requirements.  Meets the product standard's requirements.  Does not apply, since the entire switchgear needs to be evaluated.
Equipment heat dissipation, current-dependent Pvid  Heat dissipation capacity Pdiss  Heat dissipation per pole, current-dependent Pvid  Rated operational current for specified heat dissipation (In)  Static heat dissipation, non-current-dependent Pvs  10.2.2 Corrosion resistance  Meets the product standard's requirements.  10.2.3.1 Verification of thermal stability of enclosures  10.2.3.2 Verification of resistance of insulating materials to normal heat  10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects  10.2.4 Resistance to ultra-violet (UV) radiation  10.2.5 Lifting  Does not apply, since the entire switchgear needs to be evaluated.
Equipment heat dissipation, current-dependent Pvid  Heat dissipation capacity Pdiss  0 W  Heat dissipation per pole, current-dependent Pvid  0 W  Rated operational current for specified heat dissipation (In)  Static heat dissipation, non-current-dependent Pvs  0 W  10.2.2 Corrosion resistance  Meets the product standard's requirements.  10.2.3.1 Verification of thermal stability of enclosures  Meets the product standard's requirements.  10.2.3.2 Verification of resistance of insulating materials to normal heat  Meets the product standard's requirements.  10.2.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects  Meets the product standard's requirements.  Does not apply, since the entire switchgear needs to be evaluated.
Equipment heat dissipation, current-dependent Pvid  Heat dissipation capacity Pdiss  0 W  Heat dissipation per pole, current-dependent Pvid  0 W  Rated operational current for specified heat dissipation (In)  Static heat dissipation, non-current-dependent Pvs  0 W  10.2.2 Corrosion resistance  Meets the product standard's requirements.  10.2.3.1 Verification of thermal stability of enclosures  Meets the product standard's requirements.  10.2.3.2 Verification of resistance of insulating materials to normal heat  Meets the product standard's requirements.  10.2.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects  Meets the product standard's requirements.  Does not apply, since the entire switchgear needs to be evaluated.
Heat dissipation per pole, current-dependent Pvid  Rated operational current for specified heat dissipation (In)  O A  Static heat dissipation, non-current-dependent Pvs  O W  10.2.2 Corrosion resistance  Meets the product standard's requirements.  10.2.3.1 Verification of thermal stability of enclosures  Meets the product standard's requirements.  10.2.3.2 Verification of resistance of insulating materials to normal heat  Meets the product standard's requirements.  Does not apply, since the entire switchgear needs to be evaluated.
Rated operational current for specified heat dissipation (In)  Static heat dissipation, non-current-dependent Pvs  0 W  10.2.2 Corrosion resistance  Meets the product standard's requirements.  10.2.3.1 Verification of thermal stability of enclosures  Meets the product standard's requirements.  10.2.3.2 Verification of resistance of insulating materials to normal heat  Meets the product standard's requirements.  Does not apply, since the entire switchgear needs to be evaluated.
Static heat dissipation, non-current-dependent Pvs  10.2.2 Corrosion resistance  Meets the product standard's requirements.  10.2.3.1 Verification of thermal stability of enclosures  Meets the product standard's requirements.  10.2.3.2 Verification of resistance of insulating materials to normal heat  Meets the product standard's requirements.  Does not apply, since the entire switchgear needs to be evaluated.
10.2.2 Corrosion resistance  Meets the product standard's requirements.  10.2.3.1 Verification of thermal stability of enclosures  Meets the product standard's requirements.  10.2.3.2 Verification of resistance of insulating materials to normal heat  Meets the product standard's requirements.  10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects  Meets the product standard's requirements.  10.2.4 Resistance to ultra-violet (UV) radiation  Meets the product standard's requirements.  Does not apply, since the entire switchgear needs to be evaluated.
10.2.3.1 Verification of thermal stability of enclosures  Meets the product standard's requirements.  10.2.3.2 Verification of resistance of insulating materials to normal heat  Meets the product standard's requirements.  10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects  Meets the product standard's requirements.  10.2.4 Resistance to ultra-violet (UV) radiation  Meets the product standard's requirements.  Does not apply, since the entire switchgear needs to be evaluated.
10.2.3.2 Verification of resistance of insulating materials to normal heat  10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects  10.2.4 Resistance to ultra-violet (UV) radiation  Meets the product standard's requirements.  10.2.5 Lifting  Does not apply, since the entire switchgear needs to be evaluated.
10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects  Meets the product standard's requirements.  10.2.4 Resistance to ultra-violet (UV) radiation  Meets the product standard's requirements.  10.2.5 Lifting  Does not apply, since the entire switchgear needs to be evaluated.
10.2.4 Resistance to ultra-violet (UV) radiation  Meets the product standard's requirements.  10.2.5 Lifting  Does not apply, since the entire switchgear needs to be evaluated.
10.2.5 Lifting  Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 Mechanical impact Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 Inscriptions Meets the product standard's requirements.
10.3 Degree of protection of assemblies Does not apply, since the entire switchgear needs to be evaluated.
10.4 Clearances and creepage distances  Meets the product standard's requirements.
10.5 Protection against electric shock  Does not apply, since the entire switchgear needs to be evaluated.
10.6 Incorporation of switching devices and components  Does not apply, since the entire switchgear needs to be evaluated.
10.7 Internal electrical circuits and connections Is the panel builder's responsibility.
10.8 Connections for external conductors Is the panel builder's responsibility.
10.9.2 Power-frequency electric strength Is the panel builder's responsibility.
10.9.3 Impulse withstand voltage Is the panel builder's responsibility.
10.9.4 Testing of enclosures made of insulating material Is the panel builder's responsibility.
10.10 Temperature rise Not applicable.
10.11 Short-circuit rating  Is the panel builder's responsibility. The specifications for the switchgear multiple observed.
10.12 Electromagnetic compatibility  Is the panel builder's responsibility. The specifications for the switchgear multiple observed.
10.13 Mechanical function  The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

## Technical data ETIM 9.0 Low-voltage industrial components (EG000017) / Accessories/spare parts for low-voltage switch technology (EC002498) Electric engineering, automation, process control engineering / Low-voltage switch technology / Component for low-voltage switching technology (accessories) (ecl@ss13-27-37-13-92 [AKN570018]) Type of accessory/spare part Accessory Cover Yes

No

Spare part