



Data subject to change without notice. Always confirm the data is correct from the seller.

KEM 316 M2EMC 2XM25MEMC *

EMC Switches 10-1600A

- Electromagnetic compatibility ensures safe operation in environments with electromagnetic disturbance
- Tested according to EMC EN 61000-6-3:2007+A1(2011) with EMC-glands shielded power cable
- IP66
- Available in polycarbonate up to 125 A, aluminium up to 160 A and sheet steel up to 630 A
- Padlockable
- EMC cable glands included
- Door interlock with defeat mechanism
- Tested according to IEC 60947-3
- Available in 3-, 4-, 6- or 8-poles
- **Note!** Al-cables cannot be connected directly to switch terminals. For Al-cable connection please use a bi-metal cable connector, **available here**.

Technical datasheet >>

Accessories



Product details

SKU	KEM 316 M2EMC 2XM25MEMC *
AC-21 400/415 V (A)	25 A
AC-21 690 V (A)	25 A
AC-22 400/415 V (A)	16 A
AC-22 690 V (A)	16 A
AC-23 400/415 V (A/kW)	16 A / 7.5 kW
AC-23 690 V (A/kW)	16 A / 11 kW
Cable Area to Switch Terminal (only Cu) (mm2) / Bolt size	1.5-16
EAN	6419410272633
Enclosure	M2
Enclosure Type	Polycarbonate
IP Rating	IP66
Number of Poles	3
Operation	Front-operated
Switch type	Load Break Switch
Weight (kg)	0.6

Dimensional drawing

